



CLICK



SIZE
01 | 02 | 03



WATTS
10.5 | 20 | 30 | 40



BEAM ANGLES
SPOT | MEDIUM | FLOOD



INGRESS
IP 20

TECHNICAL DATASHEET

CLICK

TRACKLIGHTS

Click Tracklight collection is based on vertical & horizontal rotary design. Offered wattages are 10W - 40W in Spot, Medium & Flood beam options to adapt to site requirements within the standard color spectrums.

Luminaire can be adjusted 180° vertical and 355° in horizontal rotation. The complete range is IP20 suitable for indoor applications as offered.

Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request.



Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

Ratings



Technical Specifications

Light Source LED COB	Power Factor 0.9	Efficacy 100 lm/w
Lifespan 50000 Hrs	Dimming Triac / 0-10v / Dali	Input Voltage AC220-240V
CRI 80	Material Diecast Aluminum and Glass	

Dimensions (mm)

	A	B
Size 1	75	201
Size 2	95	201
Size 3	115	201

Available Options

Light Distribution	Watt	Lumen	Color Temp	Finishes
15 deg Spot (S) 60 deg Flood (F)	10.5	1100	2700 K	Black
	20	2100		
24 deg Medium (M)	30	3100	3000 K	
	40	4100		
			4000 K	

TECHNICAL DATASHEET

CLICK

TRACKLIGHTS

SIZE 1

DIMENSION - 75 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
CL 121 010 2 S	Black (2)	10.5	1100 lm	2700 K	15 deg
CL 121 010 3 S	Black (2)	10.5	1100 lm	3000 K	15 deg
CL 121 010 4 S	Black (2)	10.5	1100 lm	4000 K	15 deg

SIZE 2

DIMENSION - 95 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
CL 122 020 2 M	Black (2)	20	2100 lm	2700 K	24 deg
CL 122 020 2 M	Black (2)	20	2100 lm	3000 K	24 deg
CL 122 020 2 M	Black (2)	20	2100 lm	4000 K	24 deg

SIZE 3

DIMENSION - 115 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
CL 123 030 2 M	Black (2)	30	3100 lm	2700 K	24 deg
CL 123 030 3 M	Black (2)	30	3100 lm	3000 K	24 deg
CL 123 030 4 M	Black (2)	30	3100 lm	4000 K	24 deg
CL 123 040 2 F	Black (2)	40	4100 lm	2700 K	60 deg
CL 123 040 3 F	Black (2)	40	4100 lm	3000 K	60 deg
CL 123 040 4 F	Black (2)	40	4100 lm	4000 K	60 deg