



DEEP



SIZE
01 | 02 | 03



WATTS
07 | 12 | 15 | 20 | 25 |
30 | 35



BEAM ANGLES
SPOT | MEDIUM | FLOOD



INGRESS
IP 20

TECHNICAL DATASHEET

DEEP

DOWNLIGHT

Deep precision downlight collection in clean finishes offers multiple options to choose from wattages between 15W - 20W in Spot & Medium beam options and as made available across 2 varied size options to adopt to site requirements within the standard color spectrum.

Luminaire can be tilted 25° with up & down adjustment with 335° horizontal adjustment, to meet light orientation demands.

Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request.



Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

Ratings



Technical Specifications

Light Source LED COB	Power Factor 0.9	Efficacy 100 lm/w
Lifespan 50000 Hrs	Dimming Triac / 0-10v / Dali	Input Voltage AC220-240V
CRI 80	Material Diecast Aluminum and Glass	

Dimensions (mm)

	D	H	Cut Out
Size 1	85	115	75
Size 2	101	145	95
Size 3	124	165	115

Available Options

Light Distribution	Watt	Lumen	Color Temp	Finishes
10 deg Spot (S) 60 deg Flood (F)	7	501	3000 K	White
	12	875		
25 deg Medium (M)	15	1087	4000 K	
	20	1454		
	25	1812	5000 K	
	30	2196		
	35	2548		

TECHNICAL DATASHEET

DEEP

DOWNLIGHT

SIZE 1

DIMENSION - 85mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
DE 111 007 3 S	White (1)	7	501 lm	3000 K	10 deg
DE 111 007 4 S	White (1)	7	501 lm	4000 K	10 deg
DE 111 007 5 S	White (1)	7	501 lm	5000 K	10 deg
DE 111 007 3 S	White (1)	7	501 lm	3000 K	10 deg
DE 111 007 4 S	White (1)	7	501 lm	4000 K	10 deg
DE 111 007 5 S	White (1)	7	501 lm	5000 K	10 deg
DE 111 012 3 S	White (1)	12	875 lm	3000 K	10 deg
DE 111 012 4 S	White (1)	12	875 lm	4000 K	10 deg
DE 111 012 5 S	White (1)	12	875 lm	5000 K	10 deg
DE 111 012 3 S	White (1)	12	875 lm	3000 K	10 deg
DE 111 012 4 S	White (1)	12	875 lm	4000 K	10 deg
DE 111 012 5 S	White (1)	12	875 lm	5000 K	10 deg

SIZE 2

DIMENSION - 101 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
DE 112 015 3 M	White (1)	15	1087 lm	3000 K	25 deg
DE 112 015 4 M	White (1)	15	1087 lm	4000 K	25 deg
DE 112 015 5 M	White (1)	15	1087 lm	5000 K	25 deg
DE 112 015 3 M	White (1)	15	1087 lm	3000 K	25 deg
DE 112 015 4 M	White (1)	15	1087 lm	4000 K	25 deg
DE 112 015 5 M	White (1)	15	1087 lm	5000 K	25 deg
DE 112 020 3 M	White (1)	20	1454 lm	3000 K	25 deg
DE 112 020 4 M	White (1)	20	1454 lm	4000 K	25 deg
DE 112 020 5 M	White (1)	20	1454 lm	5000 K	25 deg
DE 112 020 3 M	White (1)	20	1454 lm	3000 K	25 deg
DE 112 020 4 M	White (1)	20	1454 lm	4000 K	25 deg
DE 112 020 5 M	White (1)	20	1454 lm	5000 K	25 deg

SIZE 3

DIMENSION - 124 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
DE 113 025 3 F	White (1)	25	1812 lm	3000 K	60 deg
DE 113 025 4 F	White (1)	25	1812 lm	4000 K	60 deg
DE 113 025 5 F	White (1)	25	1812 lm	5000 K	60 deg
DE 113 025 3 F	White (1)	25	1812 lm	3000 K	60 deg
DE 113 025 4 F	White (1)	25	1812 lm	4000 K	60 deg
DE 113 025 5 F	White (1)	25	1812 lm	5000 K	60 deg
DE 113 030 3 F	White (1)	30	2196 lm	3000 K	60 deg
DE 113 030 4 F	White (1)	30	2196 lm	4000 K	60 deg
DE 113 030 5 F	White (1)	30	2196 lm	5000 K	60 deg
DE 113 030 3 F	White (1)	30	2196 lm	3000 K	60 deg
DE 113 030 4 F	White (1)	30	2196 lm	4000 K	60 deg
DE 113 030 5 F	White (1)	30	2196 lm	5000 K	60 deg