



ETCH



SIZE
01 | 02 | 03



WATTS
10 | 20 | 30



BEAM ANGLES
SPOT | MEDIUM | OVAL



INGRESS
IP 20

TECHNICAL DATASHEET

ETCH

MODULAR LIGHT SURFACE

Line linear downlight collection in clean finishes offers multiple options to chose from wattages between 4W - 37W in Spot & Medium beam options and as made available across multiple arrangements to adopt to site requirements within the standard color spectrum.

Luminaire can be offered in Symmetric and Asymmeetric beam options, to meet light orientation demands.


Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request above 6W.



Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

Ratings



Technical Specifications

Light Source LED COB	Power Factor 0.9	Efficacy 100 lm/w
Lifespan 50000 Hrs	Dimming Triac / 0-10v / Dali	Input Voltage AC220-240V
CRI 80	Material Diecast Aluminum and Glass	

Dimensions (mm)

	A	B	C
Size 1	138	35	91
Size 2	271	35	91
Size 3	404	35	91

Available Options

Light Distribution		Watt	Lumen	Color Temp	Finishes
15 deg	Spot(s)	10	900	2700 K	White
30 deg	Medium (M)	20	1500		
30 deg	Medium (M)	30	2800	3000 K	Black
				4000 K	

TECHNICAL DATASHEET

ETCH

DOWNLIGHT

SIZE 1

DIMENSION -
138X35X91 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
ET 112 010 2 S	White (1)	10	900 lm	2700 K	15 deg
ET 112 010 3 S	White (1)	10	900 lm	3000 K	15 deg
ET 112 010 4 S	White (1)	10	900 lm	4000 K	15 deg
ET 122 010 2 S	Black (2)	10	900 lm	2700 K	15 deg
ET 122 010 3 S	Black (2)	10	900 lm	3000 K	15 deg
ET 122 010 4 S	Black (2)	10	900 lm	4000 K	15 deg
ET 112 010 2 O	White (1)	10	550 lm	2700 K	70 x 15 deg
ET 112 010 3 O	White (1)	10	550 lm	3000 K	70 x 15 deg
ET 112 010 4 O	White (1)	10	550 lm	4000 K	70 x 15 deg
ET 122 010 2 O	Black (2)	10	550 lm	2700 K	70 x 15 deg
ET 122 010 3 O	Black (2)	10	550 lm	3000 K	70 x 15 deg
ET 122 010 4 O	Black (2)	10	550 lm	4000 K	70 x 15 deg

SIZE 2

DIMENSION -
271X35X91 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
ET 113 020 2 M	White (1)	20	1900 lm	2700 K	30 deg
ET 113 020 3 M	White (1)	20	1900 lm	3000 K	30 deg
ET 113 020 4 M	White (1)	20	1900 lm	4000 K	30 deg
ET 123 020 2 M	Black (2)	20	1900 lm	2700 K	30 deg
ET 123 020 3 M	Black (2)	20	1900 lm	3000 K	30 deg
ET 123 020 4 M	Black (2)	20	1900 lm	4000 K	30 deg
ET 113 020 2 O	White (1)	20	1100 lm	2700 K	90 x 15 deg
ET 113 020 3 O	White (1)	20	1100 lm	3000 K	90 x 15 deg
ET 113 020 4 O	White (1)	20	1100 lm	4000 K	90 x 15 deg
ET 123 020 2 O	Black (2)	20	1100 lm	2700 K	90 x 15 deg
ET 123 020 3 O	Black (2)	20	1100 lm	3000 K	90 x 15 deg
ET 123 020 4 O	Black (2)	20	1100 lm	4000 K	90 x 15 deg

SIZE 3

DIMENSION -
404X35X91 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
ET 115 030 2 O	White (1)	30	1500 lm	2700 K	90 x 15 deg
ET 115 030 3 O	White (1)	30	1500 lm	3000 K	90 x 15 deg
ET 115 030 4 O	White (1)	30	1500 lm	4000 K	90 x 15 deg
ET 125 030 2 O	Black (2)	30	1500 lm	2700 K	90 x 15 deg
ET 125 030 3 O	Black (2)	30	1500 lm	3000 K	90 x 15 deg
ET 125 030 4 O	Black (2)	30	1500 lm	4000 K	90 x 15 deg
ET 115 030 2 M	White (1)	30	2800 lm	2700 K	30 deg
ET 115 030 3 M	White (1)	30	2800 lm	3000 K	30 deg
ET 115 030 4 M	White (1)	30	2800 lm	4000 K	30 deg
ET 125 030 2 M	Black (2)	30	2800 lm	2700 K	30 deg
ET 125 030 3 M	Black (2)	30	2800 lm	3000 K	30 deg
ET 125 030 4 M	Black (2)	30	2800 lm	4000 K	30 deg