



FIXIT


LUMALIF



SIZE
01 | 02 | 03



WATTS
10 | 15 | 20 | 30 | 35
| 40 | 45



BEAM ANGLES
SPOT | MEDIUM | FLOOD



INGRESS
IP 44

TECHNICAL DATASHEET


FIXIT

DOWNLIGHT

Fixit downlight collection is a modular arrangement to offer multiple options to choose from wattages ranging between 10W - 45W in all standard beam options and as made available across 3 varied size options to adapt to site requirements within the standard color spectrums.

Luminaire can be adjusted 30° vertical and 355° in free rotation. The complete range is IP44 suitable for indoor applications as offered.

Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request.



Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

Ratings



Technical Specifications

Light Source LED COB	Power Factor 0.9	Efficacy 100 lm/w
Lifespan 50000 Hrs	Dimming Triac / 0-10v / Dali	Input Voltage AC220-240V
CRI 80	Material Diecast Aluminum and Glass	

Dimensions (mm)

	D	H	Cutout
Size 1	85	77	75
Size 2	115	107	105
Size 3	160	152	150

Available Options

Light Distribution		Watt	Lumen	Color Temp	Finishes
15 deg	Spot (S)	10	800	2700 K	White
36 deg	Flood (F)	15	1050		
24 deg	Medium (M)	20	1650	3000 K	
50 deg	Wide Flood (W)	30	2300		
		35	3500	4000 K	
		40	3900		
		45	4300		

TECHNICAL DATASHEET

FIXIT

DOWNLIGHT

SIZE 1

DIMENSION - 85 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
FI 111 010 2 S	White (1)	10	800 lm	2700 K	15 deg
FI 111 010 3 S	White (1)	10	800 lm	3000 K	15 deg
FI 111 010 4 S	White (1)	10	800 lm	4000 K	15 deg
FI 111 015 2 S	White (1)	15	1050 lm	2700 K	15 deg
FI 111 015 3 S	White (1)	15	1050 lm	3000 K	15 deg
FI 111 015 4 S	White (1)	15	1050 lm	4000 K	15 deg

SIZE 2

DIMENSION - 115 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
FI 112 020 2 M	White (1)	20	1650 lm	2700 K	24 deg
FI 112 020 3 M	White (1)	20	1650 lm	3000 K	24 deg
FI 112 020 4 M	White (1)	20	1650 lm	4000 K	24 deg
FI 112 030 4 F	White (1)	30	2300 lm	2700 K	36 deg
FI 112 030 4 F	White (1)	30	2300 lm	3000 K	36 deg
FI 112 030 4 F	White (1)	30	2300 lm	4000 K	36 deg

SIZE 3

DIMENSION - 160 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
FI 113 035 4 F	White (1)	35	3500 lm	2700 K	36 deg
FI 113 035 4 F	White (1)	35	3500 lm	3000 K	36 deg
FI 113 035 4 F	White (1)	35	3500 lm	4000 K	36 deg
FI 113 040 2 F	White (1)	40	3900 lm	2700 K	36 deg
FI 113 040 3 F	White (1)	40	3900 lm	3000 K	36 deg
FI 113 040 4 F	White (1)	40	3900 lm	4000 K	36 deg
FI 113 045 2 W	White (1)	45	4300 lm	2700 K	50 deg
FI 113 045 3 W	White (1)	45	4300 lm	3000 K	50 deg
FI 113 045 4 W	White (1)	45	4300 lm	4000 K	50 deg