



# ICE



SIZE  
01 | 02



WATTS  
10 | 24



BEAM ANGLES  
SPOT | MEDIUM



INGRESS  
IP 20

TECHNICAL DATASHEET

# ICE

## PENDANTS

Ice Pendant collection is a unique collection suitable for vertical & horizontal orientation. Offered wattages are 10W & 24W in Spot, Medium & Flood beam options within the standard color spectrums.

The complete range is IP20 suitable for indoor applications as offered.

Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are to be checked and confirmed.



### Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

### Ratings



### Technical Specifications

Light Source <b>LED COB</b>	Power Factor <b>0.9</b>	Efficacy <b>100 lm/w</b>
Lifespan <b>50000 Hrs</b>	Dimming <b>Triac / 0-10v / Dali</b>	Input Voltage <b>AC220-240V</b>
CRI <b>80</b>	Material <b>Diecast Aluminum and Glass</b>	

### Dimensions (mm)

	A	B
Size 1	124	152
Size 2	188	185

### Available Options

Light Distribution	Watt	Lumen	Color Temp	Finishes
15 deg Spot (s) 36 deg Medium (M)	10	900	3000 K	White
	24	2160	4000 K	Black
			5000 K	

## TECHNICAL DATASHEET

# ICE

## PENDANTS

**SIZE 2**

DIMENSION -  
 $\phi$  124 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
IC 112 010 3 S	White (1)	10	900 lm	3000 K	15 deg
IC 112 010 4 S	White (1)	10	900 lm	4000 K	15 deg
IC 112 010 5 S	White (1)	10	900 lm	5000 K	15 deg
IC 122 010 3 S	Black (2)	10	900 lm	3000 K	15 deg
IC 122 010 4 S	Black (2)	10	900 lm	4000 K	15 deg
IC 122 010 5 S	Black (2)	10	900 lm	5000 K	15 deg

**SIZE 3**

DIMENSION -  
 $\phi$  188 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
IC 113 024 3 M	White (1)	24	2160 lm	3000 K	36 deg
IC 113 024 4 M	White (1)	24	2160 lm	4000 K	36 deg
IC 113 024 5 M	White (1)	24	2160 lm	5000 K	36 deg
IC 123 024 3 M	Black (2)	24	2160 lm	3000 K	36 deg
IC 123 024 4 M	Black (2)	24	2160 lm	4000 K	36 deg
IC 123 024 5 M	Black (2)	24	2160 lm	5000 K	36 deg