


# LINE

---




SIZE

01 | 02 | 03 | 04 |  
05 | 06



WATTS

04 | 08 | 09 | 13 | 25 | 37



BEAM ANGLES  
SPOT | MEDIUM



INGRESS  
IP 20

TECHNICAL DATASHEET

# LINE

## MODULAR LIGHT RECESSED

Line linear downlight collection in clean finishes offers multiple options to chose from wattages between 4W - 37W in Spot & Medium beam options and as made available across multiple arrangements to adopt to site requirements within the standard color spectrum.



Luminaire can be offered in Symmetric and Asymmeetric beam options, to meet light orientation demands.

Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request above 6W.

### Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

### Ratings



### Technical Specifications

|                                |   |                                    |
|--------------------------------|---|------------------------------------|
| Light Source<br><b>LED COB</b> | Power Factor<br><b>0.9</b>                    | Efficacy<br><b>100 lm/w</b>        |
| Lifespan<br><b>50000 Hrs</b>   | Dimming<br><b>Triac / 0-10v / Dali</b>        | Input Voltage<br><b>AC220-240V</b> |
| CRI<br><b>80</b>               | Material<br><b>Diecast Aluminum and Glass</b> |                                    |

### Dimensions (mm)

|        | A   | B  | C  | Cutout |
|--------|-----|----|----|--------|
| Size 1 | 45  | 45 | 51 | 405X37 |
| Size 2 | 76  | 45 | 51 | 272X37 |
| Size 3 | 105 | 45 | 51 | 37X37  |
| Size 4 | 147 | 45 | 51 | 68X37  |
| Size 5 | 280 | 45 | 51 | 97X37  |
| Size 6 | 413 | 45 | 51 | 139X37 |

### Available Options

| Light Distribution   | Watt | Lumen | Color Temp | Finishes |
|--|------|-------|------------|----------|
| <div style="display: flex; justify-content: space-around;"> <div style="border: 1px solid black; padding: 2px;">15 deg</div> <div>Spot (S)</div> <div style="border: 1px solid black; padding: 2px;">36 deg</div> <div>Medium (M)</div> </div> | 4    | 190   | 2700 K     | White    |
|  | 6    | 370   |            |          |
|  | 9    | 600   | 3000 K     | Black    |
|  | 13   | 940   |            |          |
|  | 25   | 1820  |            |          |
|  | 37   | 2830  | 4000 K     |          |

## TECHNICAL DATASHEET

## LINE

MODULAR LIGHT  
RECESSED

## SIZE 1

DIMENSION - 405X37

| Article Reference | Finish    | Watt | Lumen  | Colour Temp | Beam Angle |
|-------------------|-----------|------|--------|-------------|------------|
| LI 111 004 2 S    | White (1) | 4    | 190 lm | 2700 K      | 15 deg     |
| LI 111 004 3 S    | White (1) | 4    | 190 lm | 3000 K      | 15 deg     |
| LI 111 004 4 S    | White (1) | 4    | 190 lm | 4000 K      | 15 deg     |
| LI 121 004 2 S    | Black (2) | 4    | 190 lm | 2700 K      | 15 deg     |
| LI 121 004 3 S    | Black (2) | 4    | 190 lm | 3000 K      | 15 deg     |
| LI 121 004 4 S    | Black (2) | 4    | 190 lm | 4000 K      | 15 deg     |

## SIZE 2

DIMENSION - 272X37

| Article Reference | Finish    | Watt | Lumen  | Colour Temp | Beam Angle |
|-------------------|-----------|------|--------|-------------|------------|
| LI 111 006 2 S    | White (1) | 6    | 370 lm | 2700 K      | 15 deg     |
| LI 111 006 3 S    | White (1) | 6    | 370 lm | 3000 K      | 15 deg     |
| LI 111 006 4 S    | White (1) | 6    | 370 lm | 4000 K      | 15 deg     |
| LI 121 006 2 S    | Black (2) | 6    | 370 lm | 2700 K      | 15 deg     |
| LI 121 006 3 S    | Black (2) | 6    | 370 lm | 3000 K      | 15 deg     |
| LI 121 006 4 S    | Black (2) | 6    | 370 lm | 4000 K      | 15 deg     |

## SIZE 3

DIMENSION - 37X37

| Article Reference | Finish    | Watt | Lumen  | Colour Temp | Beam Angle |
|-------------------|-----------|------|--------|-------------|------------|
| LI 111 009 2 S    | White (1) | 9    | 600 lm | 2700 K      | 15 deg     |
| LI 111 009 3 S    | White (1) | 9    | 600 lm | 3000 K      | 15 deg     |
| LI 111 009 4 S    | White (1) | 9    | 600 lm | 4000 K      | 15 deg     |
| LI 121 009 2 S    | Black (2) | 9    | 600 lm | 2700 K      | 15 deg     |
| LI 121 009 3 S    | Black (2) | 9    | 600 lm | 3000 K      | 15 deg     |
| LI 121 009 4 S    | Black (2) | 9    | 600 lm | 4000 K      | 15 deg     |

## SIZE 4

DIMENSION - 68X37

| Article Reference | Finish    | Watt | Lumen  | Colour Temp | Beam Angle |
|-------------------|-----------|------|--------|-------------|------------|
| LI 111 013 2 S    | White (1) | 13   | 940 lm | 2700 K      | 15 deg     |
| LI 111 013 3 S    | White (1) | 13   | 940 lm | 3000 K      | 15 deg     |
| LI 111 013 4 S    | White (1) | 13   | 940 lm | 4000 K      | 15 deg     |
| LI 121 013 2 S    | Black (2) | 13   | 940 lm | 2700 K      | 15 deg     |
| LI 121 013 3 S    | Black (2) | 13   | 940 lm | 3000 K      | 15 deg     |
| LI 121 013 4 S    | Black (2) | 13   | 940 lm | 4000 K      | 15 deg     |

## SIZE 5

DIMENSION - 97X37

| Article Reference | Finish    | Watt | Lumen   | Colour Temp | Beam Angle |
|-------------------|-----------|------|---------|-------------|------------|
| LI 111 025 2 M    | White (1) | 25   | 1820 lm | 2700 K      | 36 deg     |
| LI 111 025 3 M    | White (1) | 25   | 1820 lm | 3000 K      | 36 deg     |
| LI 111 025 4 M    | White (1) | 25   | 1820 lm | 4000 K      | 36 deg     |
| LI 121 025 2 M    | Black (2) | 25   | 1820 lm | 2700 K      | 36 deg     |
| LI 121 025 3 M    | Black (2) | 25   | 1820 lm | 3000 K      | 36 deg     |
| LI 121 025 4 M    | Black (2) | 25   | 1820 lm | 4000 K      | 36 deg     |