


# MUNDO


TRACKLIGHTS

---


LUMALIF



SIZE  
01



WATTS  
10 | 15



BEAM ANGLES  
SPOT | MEDIUM



INGRESS  
IP 20

TECHNICAL DATASHEET

# MUNDO

## TRACKLIGHTS

TMundo Tracklight collection is based on vertical & horizontal rotary design. Offered wattages are 10W & 15W in a Spot & Medium beam option and as made available across 1 size that fits all - surface mounted, recessed or track mounted options to adapt to site requirements within the standard color spectrums.

Luminaire can be adjusted 90° vertical and 320° in free rotation. The complete range is IP20 suitable for indoor applications as offered.

Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request.



### Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

### Ratings



### Technical Specifications

Light Source <b>LED COB</b>	Power Factor <b>0.9</b>	Efficacy <b>100 lm/w</b>
Lifespan <b>50000 Hrs</b>	Dimming <b>Triac / 0-10v / Dali</b>	Input Voltage <b>AC220-240V</b>
CRI <b>80</b>	Material <b>Diecast Aluminum and Glass</b>	

### Dimensions (mm)

	A	B
Size 1	100	166

### Available Options

Light Distribution	Watt	Lumen	Color Temp	Finishes
20 deg Spot (s) 36 deg Medium (M)	10	1100	2700 K	White
	15	1550	3000 K	Black
			4000 K	

## TECHNICAL DATASHEET

# MUNDO

## TRACKLIGHTS

**SIZE 1**

DIMENSION - 100 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
TM 111 010 2 S	White (1)	10	1100 lm	2700 K	20 deg
TM 111 010 3 S	White (1)	10	1100 lm	3000 K	20 deg
TM 111 010 4 S	White (1)	10	1100 lm	4000 K	20 deg
TM 121 010 2 S	Black (2)	10	1100 lm	2700 K	20 deg
TM 121 010 3 S	Black (2)	10	1100 lm	3000 K	20 deg
TM 121 010 4 S	Black (2)	10	1100 lm	4000 K	20 deg
TM 111 015 2 M	White (1)	15	1550 lm	2700 K	36 deg
TM 111 015 3 M	White (1)	15	1550 lm	3000 K	36 deg
TM 111 015 4 M	White (1)	15	1550 lm	4000 K	36 deg
TM 121 015 2 M	Black (2)	15	1550 lm	2700 K	36 deg
TM 121 015 3 M	Black (2)	15	1550 lm	3000 K	36 deg
TM 121 015 4 M	Black (2)	15	1550 lm	4000 K	36 deg