


STELLAR

TRACKLIGHTS




LUMALIF



SIZE
01



WATTS
10 | 13 | 17 | 21



BEAM ANGLES
MEDIUM | FLOOD



INGRESS
IP 20

TECHNICAL DATASHEET

STELLAR

TRACKLIGHTS

TStellar Spherical tracklight collection with Oblique axis rotation offers multiple options to chose from wattages ranging between 10W - 20W in Medium & Flood beam options and as made available across 2 varied size options to adapt to site requirements within the standard color spectrums.

Luminaire can be adjusted 40° in free rotation upto 340°, to meet light orientation demands. Easy installation and maintenance.


Standard protocol for fixed output driver is offered in our article coding. Dimmable driver options are available on request.



Application Areas

Shopping centers, Retail outlets, Hospitals, Super markets

Ratings



Technical Specifications

Light Source LED COB	Power Factor 0.9	Efficacy 100 lm/w
Lifespan 50000 Hrs	Dimming Triac / 0-10v / Dali	Input Voltage AC220-240V
CRI 80	Material Diecast Aluminum and Glass	

Dimensions (mm)

	A	B	C	D
Size 1	120	96		

Available Options

Light Distribution	Watt	Lumen	Color Temp	Finishes
36 deg Medium (M)	10	1200	2700 K	White
38 deg Flood (F)	13	1400		
	17	1800	3000 K	Black
	21		4000 K	

TECHNICAL DATASHEET

STELLAR

TRACKLIGHTS

SIZE 1

DIMENSION - 120 mm

Article Reference	Finish	Watt	Lumen	Colour Temp	Beam Angle
TS 112 010 2 M	White (1)	10	1200 lm	2700 K	36 deg
TS 112 010 3 M	White (1)	10	1200 lm	3000 K	36 deg
TS 112 010 4 M	White (1)	10	1200 lm	4000 K	36 deg
TS 122 010 2 M	Black (2)	10	1200 lm	2700 K	36 deg
TS 122 010 3 M	Black (2)	10	1200 lm	3000 K	36 deg
TS 122 010 4 M	Black (2)	10	1200 lm	4000 K	36 deg
TS 112 013 2 M	White (1)	13	1400 lm	2700 K	36 deg
TS 112 013 3 M	White (1)	13	1400 lm	3000 K	36 deg
TS 112 013 4 M	White (1)	13	1400 lm	4000 K	36 deg
TS 122 013 2 M	Black (2)	13	1400 lm	2700 K	36 deg
TS 122 013 3 M	Black (2)	13	1400 lm	3000 K	36 deg
TS 122 013 4 M	Black (2)	13	1400 lm	4000 K	36 deg
TS 112 017 2 F	White (1)	17	1800 lm	2700 K	60 deg
TS 112 017 3 F	White (1)	17	1800 lm	3000 K	60 deg
TS 112 017 4 F	White (1)	17	1800 lm	4000 K	60 deg
TS 122 017 2 F	Black (2)	17	1800 lm	2700 K	60 deg
TS 122 017 3 F	Black (2)	17	1800 lm	3000 K	60 deg
TS 122 017 4 F	Black (2)	17	1800 lm	4000 K	60 deg
TS 112 021 2 F	White (1)	21	2100 lm	2700 K	60 deg
TS 112 021 3 F	White (1)	21	2100 lm	3000 K	60 deg
TS 112 021 4 F	White (1)	21	2100 lm	4000 K	60 deg
TS 122 021 2 F	Black (2)	21	2100 lm	2700 K	60 deg
TS 122 021 3 F	Black (2)	21	2100 lm	3000 K	60 deg
TS 122 021 4 F	Black (2)	21	2100 lm	4000 K	60 deg